



Dimensions
 Height 180mm · Width 143mm · Depth 74mm

The system consists of a wall mounted control panel. The system only requires a 240v supply. The output from the panel can be used to feed a water valve directly or a isolating contactor for electrical isolation.

Operation

Turning the keyswitch will allow the water and/or electric services to be switched on. This is indicated on the front of the panel.

Any external interfaces such as fire alarm or remote emergency stop being activated will switch the system off automatically.

The system will need to be reset.

AS PART OF THE GASGUARD RANGE OF GAS SAFETY SYSTEMS, FLAMEFAST SUPPLY A BASIC SERVICES (WATER AND ELECTRIC) ISOLATION PANEL FOR USE IN SCHOOLS.

THE SERVICE-GUARD SYSTEM IS FOR ROOMS WHERE THERE IS NO GAS OR A SEPARATE GAS SAFETY SYSTEM HAS BEEN INSTALLED.

THE SERVICE-GUARD IS SUPPLIED WITH DEDICATED REMOTE STOP AND FIRE ALARM INTERFACES.

STANDARD SYSTEM FEATURES

Remote Emergency Stop Button

Additional Emergency Stops can be fitted remotely to the control panel to isolate the services supply immediately in the event of an emergency.

Fire Alarm

The Service-Guard has a Fire Alarm interface fitted as standard which when connected to the central fire alarm system will isolate the service automatically.

FLAMEFAST (UK) LTD

Unit 2 · Labtec Street · Swinton · Manchester M27 8SE
 Tel 0161 793 9998 · Fax 0161 793 0098
 www.flamefast.co.uk · e-mail: sales@flamefast.co.uk

