



OVERVIEW

The Flamefast Mobile Bench OPTION 2 consists of one educational compliant Bench Drill and Bandfacer along with one HSG250 compliant extractor unit.

The bench is a heavy duty mobile workbench fitted with casters that incorporate a safety wind down rubber foot which acts as a locking mechanism. The frame is made up of 40mm steel box section finish baked in the Flamefast red for a vibrant finish.

All Mobile Benches are supplied fully assembled ready to plug into a single phase 16 amp Commando type socket.

Equipment comes pre wired and interlocked to extraction. Power requirement, single 16amp Commando type socket controlled by a lockable isolator switch

KEY FEATURES

- Industrial grade hardwearing castors
- Emergency Foot Stops where necessary
- All machines pre wired and ready to go
- Integrated extraction system comes with LEV Indicator
- Supplied fully assembled ready to plug into single phase 16amp commando type socket
- Interlocking (electric and extraction)
- Manufacturers 1 year warranty
- **UK Manufactured**

BESPOKE OPTION

A bespoke option is available where you can select the accompanying products as best fits your needs. To find out more about the bespoke option please contact your Flamefast representative

MOBILE BENCHES

MOBILE BENCH 02 - MB02

DRILL, BANDFACER & EXTRACTION



Specifications

Mobile Bench:

Size (L x W x H)	1500 x 750 x 850 mm
Table Top Size	1500 x 800 x 20 mm (70 with frame)
Net Weight	± 60 kg

Bench Drill:

Size (H x W x D)	815 x 372 x 627 mm
Weight	46 kg
Drilling capacity (mild steel)	16 mm
Motor	0.37 kW 1ph
Spindle	2MT
Spindle Speeds rpm 50Hz	Belt, stepped pulleys
Spindle Travel	100 mm
Throat Depth	194 mm
Column Diameter	70 mm
Base - overall	235 x 409 mm
Base - working surface	235 x 295 mm
Max distance chuck to base	294 mm


Bandsaw:

Worktable Size (W x D)	278 x 226 mm
Belt Size (WxL)	150 x 1090 mm
Belt Speed	1500 rpm
Motor	3 Phase = 1.5 kw / 1 Phase = 0.75 kw
Electrical Supply	400V/3ph/50Hz or 230V/1ph/50Hz
Weight	97 kg

Extractor B:

Rated Input Power	1200 W
Container Volume	35 L (gross) / 23 L (net) / 19.2 L (water net)
Dust Class	M
Tool Dimension (W x L x H)	375 x 515 x 575 mm
Filter Surface area	6150 cm ²
Max Airflow Rate (turbine)	74 l/s
Max Vacuum Pressure (turbine)	254 mbar
Voltage, electrical	240 V

Included Standard



1. Flamefast Mobile Bench x1
2. Bandfacer x1
3. Bench Drill x1
4. Extractor B x1
5. Stop Button x1