



| OVERVIEW |

The Flamefast Mobile Bench OPTION 6 consists of one educational compliant Wood Lathe along with a HSG250 compliant extractor unit.

The bench is a heavy duty mobile workbench fitted with casters that incorporate a safety wind down rubber foot which acts as a locking mechanism. The frame is made up of 40mm steel box section finish baked in the Flamefast red for a vibrant finish.

All Mobile Benches are supplied fully assembled ready to plug into a single phase 16 amp Commando type socket.

Equipment comes pre wired and interlocked to extraction. Power requirement, single 16amp Commando type socket controlled by a lockable isolator switch

| KEY FEATURES |

- Industrial grade hardwearing castors
- Emergency Foot Stops where necessary
- All machines pre wired and ready to go
- Integrated extraction system comes with LEV Indicator
- Supplied fully assembled ready to plug into single phase 16amp commando type socket
- Interlocking (electric and extraction)
- Manufacturers 1 year warranty
- **UK Manufactured**

| BESPOKE OPTION |

A bespoke option is available where you can select the accompanying products as best fits your needs. To find out more about the bespoke option please contact your Flamefast representative

MOBILE BENCHES

MOBILE BENCH 06 - MB06

WOOD LATHE & EXTRACTOR



Specifications

Mobile Bench:

Size (L x W x H)	1500 x 750 x 850 mm
Table Top Size	1500 x 800 x 20 mm (70 with frame)
Net Weight (table only)	± 60 kg

Wood Lathe:

Size (L x W x H)	1650 x 480 x 550 mm
Net Weight	160 kg
Distance between centres	710 mm
Headstock Taper	2 MT
Lathe Speed	50-1,250 / 150-3,750 rpm
Max Diameter	875 mm (using bed extension mounted)
Max Diameter over Bed	406 mm
Power	1.5 kW
Rating	Trade
Spindle Thread	M33 x 3.5 mm
Tailstock Ram Travel	112 mm
Tailstock Taper	2 MT
Tool Post Diameter	25.4 mm (1")
Voltage	230V

Extractor W

Size (L x W x H)	640 x 490 x 1880 mm
Weight (corded tool)	30kg
Suction connector Ø	100 mm
Extraction Rate	1000 m ³ /hr
Hose length	2500 mm
Hose Diameter	100 mm
Air capacity	1500 m ³ /h
Filling Capacity	80L
Partial vacuum	1200 pa
Motor	230 V - 400 V
Power Output	600 W
Power Supply	Electric
Power Voltage	240 V
Extractor type	Dust Extractor
Suitable Dust Class	Suitable for L Class Dust

Included Standard



1. Flamefast Mobile Bench x1
2. Metal Lathe x1
3. Cabinet x1